


mamava® Flex V1 Seismic Kit Installation Guide

service@mamava.com

(802) 347-2111



Thank you for supporting breastfeeding parents with a clean and private lactation space. Both Mamava **Flex** and XL pods have a Seismic Kit offering that anchors the pod to the floor and meets building safety requirements. If your facility requires seismic anchoring, here is an overview of what you will need to do to prepare your site before pod installation.

- 1 Seismic Kit ships separately in advance of the pod.** If you ordered a pod with a Seismic Kit addition, the Seismic Kit will be shipped to you in advance of your pod's arrival. The kit includes components for part 1 of the seismic anchoring system installation—which you will need to complete prior to the pod assembly—and part 2, which occurs as part of the pod installation. Hold onto all parts until your pod assembly is complete.
- 2 Complete part 1: Drill anchor holes, install anchors, and fasten seismic brackets to the floor.** It should take 1 person approximately 1 hour to install the Seismic Kit. You are responsible for drilling the anchor holes in the concrete floor where the pod will be placed, installing anchors, and fastening the brackets to the floor. The Seismic Kit must be installed on an even and level surface. Pod assembly—even with Mamava's paid installation services—cannot occur until this step is complete.
- 3 For pods with paid installation: Schedule pod installation and anchoring.** Once you've completed part 1, please email service@mamava.com to let us know. Mamava's certified third-party installers will contact you to schedule a time to assemble your pod and complete part 2 of the seismic anchoring system installation, ensuring the pod is properly anchored to the floor.

For pods with self installation: Complete part 2 and assemble pod onto seismic anchoring system. Once you've completed part 1, you can begin to assemble your pod foundation onto the seismic anchoring system. Please reference the Mamava Flex V1 assembly instructions and complete steps 1 and 2 under Foundation. Once the chassis is in place, return to this document to complete part 2.

Tools, Parts + Hardware

Not included



Hammer Drill with 1/2" Masonry Drill Bit



Permanent Marker



Tape Measure



Painters Tape



Eye Protection



Phillips Head #2 Screwdriver



Hammer



3/8" Drive, Deep 3/4" Hex Socket



3/8" Torque Wrench




Ratchet + 9/16" + 10 mm Sockets/Wrench




Level

Provided | PART 1


Complete prior to pod assembly



(1) Complete Flex V1 Drill Template



(4) Seismic Brackets



(8) Hilti Concrete Anchors

(Includes washer, hex nut)

Drill + Install Hilti Anchors

PART 1


TOOLS AND PARTS

- 3/8" Drive, Deep 3/4" Hex Socket
- Flex V1 Seismic Drill Template
- (8) Hilti Concrete Anchors
- Permanent Marker
- Painters Tape
- Hammer Drill with 1/2" Masonry Drill Bit
- Hammer
- Tape Measure
- Level

1. Ensure that you install the Seismic Kit on an even and level surface.

Assemble the drill template by snapping together the (6) pieces for a Mamava Flex V1.


FLEX POD TEMPLATE




2. Place the drill template in the center of the desired pod location based on the placement recommendations in [Preparing for Your Mamava](#). Reminder: the seismic anchoring system requires drilling into a concrete floor.

For ease of assembly and future service needs, allow for 31" to the left and right of the template, 26" behind the template, and 39" in front of the template for Flex pods.


The power cord comes out of the back lower left of the pod, just above the floor. Be sure Flex pods are placed within 4' of a standard GFCI outlet.



3. Place a seismic bracket into each of the slots on the ends of the drill template. Ensure that the brackets open up away from the center of the pod as shown in the image.



4. Use a permanent marker to mark the (8) bracket anchor hole locations on the floor.



5. Remove the drill template. The (8) bracket anchor hole locations should be visible on the floor.


6. Wrap a piece of painters tape around the drill bit 2 5/8" from the tip of the drill for a depth marker.

Use a hammer drill with a 1/2" masonry bit to drill anchor holes into each of the (8) locations marked on the floor. Stop drilling once the tape on the drill makes contact with the floor.

Ensure the drill bit stays vertical throughout drilling.

7. Use your hammer to insert each of the (8) Hilti anchors into the pre-drilled anchor holes in the concrete floor. Be sure to make contact with the threaded end of the screw and NOT the nut. Stop hammering when the Hilti concrete anchor comes to rest.

8. Remove the 1/2" nut and washer from the top of the Hilti anchor using the ratchet and 3/4" deep hex socket.



Fasten Brackets to Floor

PART 1


TOOLS AND PARTS

- (4) Seismic Brackets
- Torque Wrench
- 3/4" Hex Socket

1. Align the holes in the brackets with the Hilti anchors in the concrete floor and drop into place. Ensure you are using the same orientation as when you marked the holes.

2. Secure the bracket by threading the Hilti nut and washers into the anchor. Use the 3/4" socket on a torque wrench (with torque set to 50 ft/lb) to tighten the (8) Hilti nuts and secure the anchor in place.

3. To comply with OPM-0733, testing and special inspection of expansion anchors shall be performed by an approved independent agency employed by the facility owner per CBC §1704A, §1910A.5, AND CAC 7-149. All reports shall be sent to the inspector of record, owner and the architect or engineer in responsible charge. To complete the testing: After installation, wait 24 hours. Then, using a calibrated torque wrench, test 50% (4 of the 8 Hilti anchors) to ensure that at 50ft-lb the nut does not move more than 1/2 turn.



STOP

For pods with paid installation: Once you've drilled the holes and installed the anchors and seismic brackets, please email service@mamava.com to let us know. Mamava's certified third-party installers will contact you to schedule a time to complete the pod installation onto the bracketing system and ensure it's properly anchored. Your work is done! ***Please store the part 2 components and have them available for the installers. We also recommend placing the drill template back on the floor and blocking off the area for safety until the pod assembly is complete.***

For self-installed pods: Please reference the Mamava Flex V1 Assembly Instructions and complete steps 1 and 2 under Foundation. Return to this document once the floor and chassis are in place to complete the pod assembly and seismic anchoring. ***If you are not continuing the assembly process immediately, please store the part 2 components and have them available when you return to assembly. We also recommend placing the drill template back on the floor and blocking off the area for safety until the pod assembly is complete.***

Assemble Floor + Chassis

PART 2



TOOLS AND PARTS

- Phillips Head Screwdriver
- Ratchet + 10 mm Socket
- Ratchet + 9/16" Socket


1. Follow pod assembly instruction steps 1 and 2 in the Foundation chapter of the Flex V1 Assembly Guide.

2. Center the floor between brackets, ensure the front flange is oriented in the position the door will face.


3. Remove caster wheels from chassis using a Phillips head screwdriver and ratchet + 10 mm socket to remove the 8 M6 screws, lock washers and nuts (4 per caster wheel).




4. Using the ratchet + 9/16" socket, extend leveling feet all the way to the lowest position.




5. Place chassis over the brackets so that the leveling feet go into the wide end of the bracket slot.



6. Tip the chassis up. Slide the leveling foot into the bracket, and ensure the chassis clears the top of the floor flange.




7. Tip the chassis back down over the floor flange.



8. Raise the leveling feet by about 10 full turns in order to drop the chassis back down to the floor.

Repeat steps 3-8 for other side of chassis.

Resume pod installation instructions in the manual for Flex V1 at step 3.



DON'T FORGET

If you're listing this pod on the free Mamava app—so breastfeeding parents can find it using Mamava's Smart Access—please send photos of the installed pod to fulfillment@mamava.com.

Notes

Need assistance? Visit help.mamava.com or contact service@mamava.com • (802) 347-2111

Learn about **service plans** to help protect your pod at mamava.com/service.